Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Previously Presented) A method comprising:

preparing, at a first unit in a source device, first information to be transmitted to a destination across network link with a pre-determined reliability requirement, wherein the source device comprises a mobile device, and wherein the destination comprises a home network;

separately preparing, at a second processing unit in the source device separate from the first processing unit, second information to be transmitted to the destination, wherein the second information does not have a pre-determined reliability requirement; and

preparing, at a stream processing unit in the source device, a data stream comprising the first and the second information to be transmitted across the network link.

- 2. (Previously Presented) The method of claim 1 further comprising aggregating first and second information sent from applications into the data stream.
- 3. (Previously Presented) The method of claim 1 in which preparing the first information includes framing the first information.
- 4. (Previously Presented) The method of claim 1 in which preparing the second information includes framing the second information.

- 5. (Previously Presented) The method of claim 1 in which preparing the first information includes processing the first information according to a transmission requirement of the source device.
- 6. (Previously Presented) The method of claim 1 in which preparing the first information includes processing the first information according to a transmission requirement of the network link.
- 7. (Previously Presented) The method of claim 1 in which preparing the second information includes processing the second information according to a transmission requirement of the source device.
- 8. (Previously Presented) The method of claim 1 in which preparing the second information includes processing the second information according to a transmission requirement of the network link.
- 9. (Previously Presented) The method of claim 1 further comprising, at a destination side of the network link, deframing the first information.
- 10. (Previously Presented) The method of claim 1 further comprising, at a destination side of the network link, deframing the second information.
- 11. (Previously Presented) The method of claim 1 further comprising, at a destination side of the network link, removing the preparations from the first information.

12. (Previously Presented) The method of claim 1 further comprising, at a destination side of the network link, removing the preparations from the second information.

13 - 15 (cancelled)

- 16. (Previously Presented) An article comprising:
- a machine readable medium which stores machine executable instructions, the instructions causing a machine to:

prepare, at a first unit in a source device, first information to be transmitted to a destination across network link with a pre-determined reliability requirement, wherein the source device comprises a mobile device, and wherein the destination comprises a home network;

separately prepare, at a second processing unit in the source device separate from the first processing unit, second information to be transmitted to the destination, wherein the second information does not have a pre-determined reliability requirement; and

prepare, at a stream processing unit in the source device, a data stream comprising the first and the second information to be transmitted across the network link.

- 17. (Previously Presented) The article of claim 16 in which preparing the first information includes framing the first information.
- 18. (Previously Presented) The article of claim 16 in which preparing the second information includes framing the second information.

- 19. (Previously Presented) The article of claim 16 in which preparing the first information includes processing the first information according to a transmission requirement of the source device.
- 20. (Previously Presented) The article of claim 16 in which preparing the first information includes processing the first information according to a transmission requirement of the network link.
- 21. (Previously Presented) The article of claim 16 in which preparing the second information includes processing the second information according to a transmission requirement of the source device.
- 22. (Previously Presented) The article of claim 16 in which preparing the second information includes processing the second information according to a transmission requirement of the network link.
 - 23. (Previously Presented) A system comprising:
- a first mechanism located at a first side of a network link and configured to:

prepare first information included in a stream of information that requires reliable transmission from a source to a destination for transmission across the network link, wherein the source comprises a mobile device, wherein the destination comprises a home network, wherein the reliable transmission comprises a pre-determined reliability requirement,

separately prepare second information included in the stream that does not require reliable transmission to the destination for transmission across the network link, and

prepare the stream for transmission across the network link; and

a second mechanism located at a second side of the network link and configured to:

handle preparations made to the stream at the first side in order to prepare the first information and the second information included in the stream for delivery to the destination.

- 24. (Previously Presented) The system of claim 23 in which preparing the first information and the second information includes framing the first information and the second information.
- 25. (Previously Presented) The system of claim 23 in which preparing the first information and the second information includes processing the first information and the second information according to a transmission requirement of the source.
- 26. (Previously Presented) The system of claim 23 in which preparing the first information and the second information includes processing the first information and the second information according to a transmission requirement of the network link.
 - 27 -30 (cancelled)
 - 31. (Previously Presented) An article comprising:

a machine readable medium which stores machine executable instructions, the instructions causing a machine to:

processing reliable information, wherein the reliable information is configured to require a pre-determined reliability requirement for transmission;

frame the reliable information; processing unreliable information: frame the unreliable information; and

processing the reliable information and unreliable information to be sent on a stream of information, wherein the unreliable information is configured for a reduced processing requirement than a processing requirement for the reliable information.

- 32 (Previously Presented) The article of claim 31, wherein the unreliable information is configured to not require a predetermined reliability requirement for transmission.
- 33. (Previously Presented) The article of claim 31, wherein framing the reliable information comprises preparing the reliable information for transmission using a transmission protocol.
- 34 (Previously Presented) The article of claim 31, wherein the unreliable information is configured to use a lower amount of processing resources than the reliable information.
- 35 (Previously Presented) The article of claim 31, wherein the processing of the reliable information comprises:

maintaining an order of framing;

forwarding the unreliable information to an unreliable packet fragmenter; and

forwarding framed reliable information and control information associated with the framed reliable information to a lower layer processing unit for the unreliable information processing.

36 (Previously Presented) The article of claim 35, wherein the unreliable information processing comprises:

framing the processed unreliable information, control information associated with the processed unreliable information, and unreliable packet fragments; and

forwarding the framed processed unreliable information, control information associated with the processed unreliable information, unreliable packet fragments, framed reliable information, and control information associated with the framed reliable information to a master stream processing unit.

37 (Previously Presented) The article of claim 36, further comprising instructions causing the machine to:

process the stream of information; and send the stream of information to the home network.

38 (Previously Presented) An article comprising:

a machine readable medium which stores machine executable instructions, the instructions causing a machine to:

receive a stream of information comprising reliable information and unreliable information, wherein the reliable information is configured to require a pre-determined reliability requirement for transmission;

handling the unreliable information, wherein handling the unreliable information comprises:

> collecting unreliable information packets; deframing the unreliable information packets; and

forwarding the unreliable information packets and . control information associated with the unreliable information to a first destination in the home network; and handling the reliable information, wherein handling the reliable information comprises:

collecting reliable information packets; deframing the reliable information packets; and forwarding the reliable information packets and control information associated with the reliable information to a second destination in the home network.

- 39 (Previously Presented) The article of claim 38, wherein the forwarding of the unreliable information occurs prior to the forwarding of the reliable information.
- 40 (Previously Presented) The article of claim 38, wherein the forwarding of the reliable information occurs prior to the forwarding of the unreliable information.
- 41 (Previously Presented) The article of claim 38, wherein the handling of the unreliable information is not dependent on the handling of the reliable information.
- 42 (Previously Presented) The article of claim 38, wherein the unreliable information is configured to require a lower amount of handling operations than the reliable information.